

Rhenocoll Anti Graffiti Cleaner AGC 7

Art. No.: A5157

Specifications: Liquid paint remover, especially for graffiti. For the removal of paint on masonry, mineral surfaces (e.g. plaster, etc.) as well as on many absorbing and non-absorbing surfaces. Bio-degradable. Suitable for the cleaning of retroreflective traffic sign foil. For professional use.

Application: Apply Rhenocoll Anti Graffiti Cleaner AGC 7 undiluted by brush, roller or spray bottle. Work from top down. Before use, wet area below the graffiti well with water.

Attention: Do not wet the area which is to be cleaned. Cleaner can only be neutralized by water, which means: no effect on wet surfaces! Leave cleaner for 5 minutes until the paint starts to curl. If necessary, rub in softly with a brush. Afterwards, wash off with water. Keep washing, until the water becomes pH-neutral. Use pressure washer to remove persistent dirt/graffiti.

Technical data:

Storage: Up to 12 months in original container, frost-free, dry and cool
pH-value: Ca. 6-8
Composition: Alcohol and washing active substances
Consumption: Depending on degree of pollution, 1 Liter for 5-10 m².
Note: Check tolerance before use

Labeling according to regulation (EC) No 1272/2008:

DANGER – H317, H318, H335, H411

GGVS/ADR: Non dangerous goods

Safety advice: During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the safety data sheet.

Supply units:

10 liter canister
20 liter canister
200 liter barrel

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case. With the release of this Technical Data Sheet all previous versions become obsolete.