

Rhenocoll Imprägnierlasur 52 S, translucent coating for wood


Art.-No.: A 6052 (colorless and colors)

Art.-No.: A 6053 (base C)

Specification: Thin-layer forming coating with higher solids content. Water-based, for interior and exterior timber without contact to the ground, timber houses, beams, balconies, façade paneling, cladding, decks, building elements, windows and doors. For garden timber, pergola, wooden screens, fences. Its pigmentation provides high UV-protection; with levelling effect, environmentally friendly and of neutral odor. Fast drying, emphasizes the grain, permeable. 2-3 coats are sufficient as final coating.

Application: By brush, dipping, flow-coating.

Preservation: Our specific raw material selection makes the conventional equipment against bacteria, mold, fungi, and putrefactive agents unnecessary.

Self-immunizing	❖	Natural	❖	Mineral
<ul style="list-style-type: none">✓ Designed for professional use✓ No carcinogenic ingredients✓ Free of Isothiazolones – free of microplastics✓ Totally harmless to humans and animals✓ Acts as an active protection of the environment, water, soil by conscious avoidance of toxic substances✓ Protected by a worldwide patent				 <p>Protective shield the natural immunization</p>

Supply form: Available in colorless and translucent wood colors.
According to color chart: Design Collection 8 (wood glaze)

Degree of gloss: Satin-matt to satin-glossy, depending on application thickness

Substrate: All soft- and hardwood

Further treatment: Several coats with Rhenocoll Imprägnierlasur 52 S possible;
2- 3 coats recommended.

Consumption: Approx. 120 - 160 ml/m²

VOC: Cat. E / base Wb / max. value 130g/L / actual value 16 g/L

Ordinance on biocidal products: Not subjected to registration, free from biocides.

Processing:

Processing consistency: Undiluted
Thinning: With water
Cleaning of tools: With water
Processing temperature: Not below 8°C (material and room temperature)

Technical Data Sheet

Rhenocoll Imprägnierlasur 52 S

Art.-No.: A 6052



Version: 2018/04 page 2 of 2

Drying time:	Depending on application strength and temperature, at normal climate, can be re-coated after 30-120 minutes
Coatings:	<u>Exterior:</u> at least 2 coats undiluted; when exposed to heavy weathering 3 coats are recommended.
General note:	Stir well before use and after longer periods of non-use. Do not mix with solvent-based materials. Substrate must be clean, dry, free from grease and wax
Weather resistance:	Rhenocoll Imprägnierlasur 52 S <u>colorless</u> is not recommended for exterior use.
Flash point:	None.

Further notes on processing:

Pre-treat dry cracks of the wood carefully. Process undiluted. Odorless after drying. Processing in well ventilated rooms.

Labeling according to regulation (EG) No. 1272/2008: No labeling required.

ADR/GGVS: Non dangerous goods.

Safety Notes: During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the safety data sheet. For professional use.

Storage: Store in the original container not below +8°C. Do not store or transport above +30°C for longer periods of time. Re-close firmly. Can be stored for 1 year in the unopened original container. Use product quickly, once container has been opened.

Supply units:

750 ml tin
2.5 l pail
5 l pail
20 l pail

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case. With the release of this Technical Data Sheet all previous versions become obsolete.