

Rhenocoll Aquaseal 4101.1, varnish for furniture, colorless, water-based

Rhenocoll Aqua- **Klassik** Industrial product

Art. no.: A 4153

Specifications: Single component varnish based on acrylate. For universal use. For interior works, furniture, panels and doors. Can be used as a primer and as a top coat. Low-emission, no blocking, good filling properties, scratch resistant. Resistant against water and common cleaning agents. Water-based, eco-friendly.

Application: By spray device. For professional use.

Delivery form / Color: Colorless.

Degree of gloss:

10 = glossy 12 = silk-glossy
14 = silk-matt 17 = matt 19 = dull matt

Substrate: Maple, beech, alder, oak, spruce, etc. Veneer and board material made of wood, chipboards, MDF.

Follow-up treatment: Rhenocoll Aquaseal 4101.1 can be used as primer and top coat.

Consumption: 150 ml/m² per spray application

VOC 2010: n/a

Labeling: No labeling required

Safety advice: During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the safety data sheet.

Storage:

Keep container firmly closed. Store cool and in a well ventilated area. Open and handle carefully. Protect from heat and direct sunlight. Do not store at temperatures below 5°C and above 25°C.

Supply units:

5 l pail
20 l pail
150 l barrel

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case. With the release of this Technical Data Sheet all previous versions become obsolete.