

Rhenocoll Aquatop 4201 Premium, parquet lacquer, colorless, water-based
Rhenocoll Aqua **Premium** Industrial Product
Art. No.: A 4246

Specifications: 1-component lacquer based on acrylate polyurethane. Ready for use. To be used as a primer and top coat. Can be used as high-quality surface treatment for stairs, hardwood and cork floors, planks, furniture and all interior timber. High to very high wear for flooring areas. Can be used with hardener 4205 for very high wear of all highly frequented public areas. Aquatop 4201 Premium is tested according to EN71 (suitable for toys) and DIN 53 160 (saliva and sweat proof). Resistant against water and common cleaning agents. Water-based, eco-friendly.

Mixing: Mix with Aquatop 4201 Premium, at a ratio of:
1 part Aquatop hardener 4205 with 10 parts Aquatop 4201 Premium.

Application: By roller, brush, spraying device. Can be used as 1-component lacquer or 2-component lacquer for areas of very high demands. When used as 2-component lacquer – mix with hardener 4205. For professional use.

Properties: In-can preservation

Delivery form / Color: Transparent, colorless

Degree of gloss: No.: 17 = matt (standard)

Substrate: Stairs and parquet, planks out of soft and hard woods. Veneer boards, chipboard, MDF.

Follow-up treatment: Aquatop 4201 Premium can be used as a primer and top coat.

Consumption: 100-120 ml/m² per application. 3-4 coats recommended.

VOC directives 2010: Cat E / base wb / max value 130 g/l / actual value 105 g/l

Labeling:
No labeling

Safety advice:
During processing, common protection measures and regulations according to the authorized trade association must be observed. Safety-relevant data and instructions regarding disposal can be found in the safety data sheet.

Storage:
Keep container firmly closed. Store cool and in a well ventilated area. Open and handle carefully. Protect from heat and direct sunlight. Do not store at temperatures below 5°C and above 30°C.

Supply units:

Rhenocoll Aquatop 4201 Premium	Rhenocoll Aquatop Härter 4205
750 ml can	250 ml can
2.5 l pail	500 ml can
5 l pail	1 l can
20 l canister	3 l canister
150 l barrel	

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.