

Rhenocoll Egalisator W- 30

Water-based, colorless

Art. no.: A 4065

Application area: Rhenocoll Egalisator W – 30 for highly absorbing surfaces to balance irregular absorption. For professional use.

Specifications:

Rhenocoll Egalisator W – 30 has a good penetration effect and allows moisture regulations. Eco-friendly and of neutral odor. For the treatment of all soft and hard woods. Fast drying. The leveling feature allows a smooth follow-up coat. Especially for colored follow-up coatings. In case of dipping only use immersion basins which do not rust. With leveling effect, decreases the risk of stains.

VOC 2010: Cat G / base wb / max value 30 g/L / actual value 20 g/L

Processing:

Application:	dipping, flooding, painting, spraying
Processing consistency:	undiluted
Viscosity:	11 sec (flowcup 4mm)
Thinning:	with water
Cleaning of tools:	with water or universal thinner
Cleaning of varnishing plant:	rinse with water, before longer pauses (weekend) also clean with solvents.
Processing temperature:	not under 8° C (material and ambient temperature)
Drying at normal climate:	20° C, 65 – 75 % humidity, according to spread strength. After 30 – 120 min able to grind, after 4 hours consequence construction possible.
Application amount:	according to absorbency of the wood 80 – 150ml/m ² s
Storage:	cool, but frost-free, store containers well. Original container storable for 12 months.
General hint:	stir before application and after longer breaks, do not mix with solvent-containing products
Flash point:	not applicable
Hazard class:	no labelling required
VbF:	not applicable
Gef. Stoff V:	no labelling required
GGVS / ADR:	no labelling required

Coating structure:

Components of soft- and hardwood

Dedust the component. Wash resin and sticky surfaces with universal thinner 140.

Apply Egalisator W – 30 on raw timber.

The following coating can be made with water based products from the product range “Aquaseal” or “Decorwachs Karbauba”

Safety advice:

Keep under lock and out of reach of children. Avoid contact with eyes. In case of contact with eyes, rinse thoroughly with water.
Please observe the safety data sheet.

Supply units:

5 liter container
25 liter container
150 liter barrel

Disposal:

Not solidified or dried up product-remains to be detoxified as special-waste. (Key No. 55508, in accordance with TA-waste). Solidified or dried up product-remains can be detoxified after key No. 55513 in accordance with TA-waste. Emptied packages are to be supplied the recycling.

Ecology:

WGK: 1 (Self-ranking)
Do not let into water, sewages or soil.

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0
Fax: ++49 (0)6384 99 38 - 112
Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.