

Rhenocoll PUR- Siegel, furniture lacquer, colorless

Rhenocoll solvent-**Klassik** Industrial product

Art. No.: A 4149

Specifications: Single component lacquer based on polyurethane, ready for use, fast-drying and PVC-steady. Great resistance against chemical and mechanical stress. High-quality refining of wooden surfaces. Resistant against many impacts such as water, dirt, grease, oil and different solvents such as ink, thinned acids and leach.

Application: by brush, spraying device or by pouring.
For professional use.

Features: preservative free.

Delivery form/Color: Transparent, colorless

Degree of gloss:

Standard: no.: 4214 = satin matt
Special adjustments: no.: 4210 = glossy
no.: 4212 = satin-gloss
no.: 4217 = matt

Substrate: All hard and soft woods. Veneers and board material made of wood, chipboards, MDF.

Further treatment: PUR-Siegel 1-K can be used as a primer and as a final coat.

Consumption: 150 ml/m² (per application)

VOC 2010: n/a

Labeling:

GefStoffV: UN 1263 paint, 3, II, ADR

Safety advice:

F highly flammable
Xn harmful
contains toluene

R-phrases:

11 highly flammable
20 Harmful by inhalation.
36/38 Irritant to eyes and skin.
48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
63 Possible risk of harm to the unborn child.

S-phrases:

53 Avoid exposure – obtain special instructions before use.

- 13 Keep away from food, drink and animal feeding stuffs.
- 16 Keep away from sources of ignition – no smoking.
- 33 Take precautionary measures against static discharge.
- 36/37 Wear suitable protective clothing and gloves.
- 51 Use only in well ventilated areas.

Storage:

Keep container firmly closed and store cool and at a well ventilated area. Open and handle with precaution. Protect from heat and direct sunlight. Do not store at temperatures below 5°C and not above 30°C.

Supply units:

- 5 ltr. canister
- 30 ltr. canister
- 200 ltr. barrel

Disposal:

Not fully hardened or dried product residue is to be disposed of as special waste (AVV waste key no. 08 01 11). Empty packaging is to be recycled.

Ecology:

Water hazard class: WGK 2

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.