

Rhenocoll PUR-Siegel Weißlack, wood lacquer, white

Rhenocoll Solvent-**Klassik** Industrial product

Art. no.: A 4139

Specifications: 2-component lacquer based on polyurethane, ready for use after mixed with hardener, fast drying and PVC-stable. Great resistance against chemical and mechanical strain. For high-quality refinement of wooden surfaces, such as seating furniture, tables, laboratory and school furniture. Resistant against many impacts such as water, dirt, grease, oil and different solvents such as acetone, ink, thinned acids and alkalis.

Application: By brush, spray device or by pouring. Must be mixed with PUR-Hardener 4002 (Mixing ratio: hardener 1:10 lacquer). For professional use.

Properties: Preservative free.

Delivery form / Color: White, opaque.

Degree of gloss: No.: 4014 = satin matt

Substrate: All soft and hard woods. Veneers and board material made of wood, chipboards, MDF.

Follow-up treatment: PUR-Siegel Weißlack can be used as a primer or top-coat.

Consumption: 150 ml/m² per spray application

VOC 2010: n/a

Labeling:

GefStoffV: UN1263 paint, 3, II, ADR

Safety advice:

F highly flammable
Xn harmful
Contains toluene

R-phrases:

11 Highly flammable
20 Harmful by inhalation
36/38 Irritant to eyes and skin
48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation
63 Possible risk of harm to the unborn child

S-phrases:

53 Avoid exposure – obtain special instructions before use
13 Keep away from food, drink and animal feeding stuffs
16 Keep away from sources of ignition – no smoking

- 33 Take precautionary measures against static discharge
36/37 Wear suitable protective clothing and gloves
51 Use only in well ventilated areas

Storage:

Keep container firmly closed and store cool and at a well ventilated area. Open and handle with precaution. Protect from heat and direct sunlight. Do not store at temperatures below 5°C and above 30°C.

Supply units:

PUR-Siegel Weißlack

- 1 l can
5 l pail
20 l pail

PUR-Härter 4002 (hardener)

- 500 ml bottle
3 l canister
30 l hobbock

Disposal:

Not fully hardened or dried product residue is to be disposed of as special waste (AVV waste key no. 08 01 11). Empty packaging is to be recycled.

Ecology:

WGK (water hazard class): 2

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.