

Aqua-Sperrgrund, GI 16- F Konzentrat, colorless, primer **Art. No: A 2542**

Specification: Colorless safety primer, preferably for interior use, also for exterior. For non-absorbing surfaces. With good blocking properties for the insulation of ingredients from the subsurface. Especially suited for the treatment of plasterboard, pressboards, hard fiber, plywood and other substrates out of cellulose. Prevents discoloration. Please dilute concentrate 1:1 with water before processing. Ecologically friendly, water-based. For professional use.

Application: by roller or brush

Supply form/color: colorless

Substrate: Suitable for non-absorbing substrates, especially plasterboard, pressboards, hard fiber and plywood.

Further processing: Wall and facade paint, plaster

VOC 2010: cat H /base wb / max value 30g/L / actual value 12g/L

Application:

Processing: must be diluted with water 1:1

Processing condition: room and object temperatures not below 8° C

Consumption: approx. 10 m²/liter. Surfaces with great absorption accordingly less.

Drying time: May be re-coated after 1 – 2 hours after drying at 20°C and 65% humidity. Fully dry and sustainable after approx. 3 days. Drying time will be increased at lower temperature and higher humidity.

General note: Stir before use or after long breaks. Do not mix with solvent-based products.

Flashpoint: n/a

Hazard class: No labeling required

VbF class: not applicable

Gef. Stoff V: no labeling required,

GGVS / ADR: no labeling required

Pre-treatment of substrate:

The substrate must be clean, dry and free of separative substances. Please observe VOB, part C, according to DIN 18363, para. 3

Storage:

Store in original containers not below +10°C and do not store or transport for a longer period of time above + 30°C. Seal well. Unopened original container can be stored for 12 months.

Packaging sizes:

5 liter pail
25 liter canister
150 liter barrel

Disposal:

Not fully dried and dried paint residue must be disposed of as special waste. (AVV-waste code 030202). Recycle empty containers.

Ecology:

WGK = 1 (Self-classification). Do not discharge into the drains / surface waters / groundwater.

Safety notes:

Keep under lock and out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, wash thoroughly with water

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0

Fax: ++49 (0)6384 99 38 - 112

Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.