

Fubocryl AB 75, floor paint
Art.-No.: A 5100

Specification: High quality floor paint based on styrene acrylate, non-aging, of low odor. Classification for painters & decorators. Hard-wearing, elastic, silky-matt acrylic paint, for weather resistant coatings onto wood or mineral substrates such as brickwork, balconies, flower pots, cement asbestos claddings, as well as wipe resistant coatings onto floor surfaces not constantly wet, such as cellar rooms, etc. Also resistant against heating oil. Bridges hair cracks. Not suitable for garages, does not resist tyres. Ecologically friendly, water – based.

Application: by brush, roller or spray-gun. For professional use.

Supply form/Color: beige and grey. Matt.

Substrate: Exterior, plaster, concrete, brickwork, lime sand brick, asbestos cement, mineral substrates. For renovating purposes with excellent adhesion onto sustainable and matt dispersion coats.

Post treatment: not applicable

VOC directives 2010: cat D /base Wb /max value 130g/L /actual value 45g/L

Application:

Processing condition:	Air- and object temperatures must not fall below 8° C
Consumption:	approx. 7 m ² /liter per single paint coat/ approx. 200ml/m ² per process on level-flat surface. On rough surface accordingly more.
Drying time:	May be varnished after 4 – 6 hours after drying at 20°C and 65% humidity. When lower temperature and higher air humidity the drying process becomes longer.
General hint:	Stir before use or long breaks. Do not mix in solvent products.
Flashpoint:	n/a
Hazard class:	No labeling VbF class: not applicable Gef. Stoff V: no labeling required, GGVS / ADR: no labeling required

Subsurface pretreatment:

Preparation: The subsurface must be clean, dry and free of separative substances. Note VOB, part C, Regard DIN 18363. Absorbent, lightly sanding substrates should be coated with Rhenocoll Aqua Tiefgrund.

Base or intermediate coating: Fubocryl diluted max.10% water.

Final coating: Fubocryl diluted max. 5% water

Storage:

Do not transport original containers not below +10°C and do not store for a longer period of time above + 30°C. Seal well. An unopened original container storable for 6 months.

Packing size:

2.5 liter container
5.0 liter container

Disposal:

Not fully dried and dried paint remains must be disposed as special waste. (AVV- waste code 030202). Recycle empty containers.

Ecology:

WGK = 1 (Self-classification). Do not discharge into the drains / surface waters / groundwater.

Safety hints:

Keep under lock and out of reach of children. Avoid contact with skin and eyes. In case of contact with eyes, wash thoroughly with water

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0
Fax: ++49 (0)6384 99 38 - 112
Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.